



CS-761BS-B / CS-761BS-W

2-Way Weatherproof Music Horn speaker



**Horn speaker for high sound quality
for BGM and PA – even outdoors.**

We supply sound, not equipment.
www.toa.eu

CS-761BS-B / CS-761BS-W

2-Way Weatherproof Music Horn speaker

The CS-761B is a compact 2-way weatherproof speaker system designed for high efficiency, high power input handling capacity, and is a high intelligible speaker suited for public address announcement and BGM application in outdoor environments. The external speaker component is finished to ensure the unit's weatherproof ability, and special paint coat prevents color degradation, ensuring its long-lasting exterior condition. This model is designed with a rotary switch that facilitates hassle-free impedance change.

FEATURES

- ✔ Horn speaker for high sound quality for BGM and PA
- ✔ Voice alarm certification EN54 under preparation
- ✔ High sound pressure: 117 DB
- ✔ All weather durability, be it water or dust. Ideal for semi-outdoor and outdoor applications.
- ✔ Rotary switch facilitates hassle-free impedance change
- ✔ Special paint coat prevents color degradation, ensuring long-lasting exterior condition.
- ✔ Various mounting brackets available as accessories allowing flexibility of mounting the speaker on a platform, in the ceiling, on the wall or on a pole.
- ✔ EN 54-24 under preparation

APPLICATIONS



Stations and platforms



Car parks



Amusement parks



Supermarkets



Schoolyards



Outdoor dining



Factories



Sport locations

SPECIFICATIONS

	CS-761BS-B / CS-761BS-W
Rated input	60W
Rated Impedance	100 V line: 170 Q (60 W), 330 Q (30 W), 670 Q (15 W), 1.3 kQ (7.5 W) 70 V line: 83 Q (60 W), 170 Q (30 W), 330 Q (15 W), 670 Q (7.5 W)
Sensitivity	100 dB (1 W, 1 m) (1 kHz - 10 kHz, pink noise)
Frequency Response	100 Hz - 20 kHz
Speaker Component	Low frequency: 16 cm (6") cone-type, High frequency: 2.5 cm (1 ") tweeter
Directivity Angle	Horizontal: 90°, Vertical: 80°
Operating Temperature	-10° C to +50° C (14°F to 122°F)
Dust/Water Protection	IP66
Connection	Ceramic Terminal, Thermal Fuse
Finish	Black / White (RAL 9001 equivalent)
Dimensions	388 (W) x 310 (H) x 367 (D) mm (15.28" x 12.2" x 14.45")
Weight	7.6 kg (16.75 lb)
Option	Speaker mount bracket: SP-201, Pole band: YS-60B, Speaker stand: ST-34B

TOA Electronics Europe GmbH

www.toa.eu

Specifications are subject to change without notice.

Printed in Germany (2106) L833TEECXXX QJ