

unbalanced

**IY204**

**Unbalanced Stereo Patch Cable**

- extremely flexible
- compact construction (4.0 mm x 8.0 mm)



<b>Conductor</b>	stranded bare copper, 7 x 0.20 mm
<b>Cross Section</b>	0.22 mm <sup>2</sup>
<b>Core Insulation</b>	PE
<b>Single Core Shielding</b>	bare copper spiral shield
<b>No. of Cores</b>	2
<b>Core Arrangement</b>	parallel, separable
<b>Outer Jacket</b>	PVC, matt
<b>Dimensions</b>	4.0 x 8.0 mm
<b>Min. Bending Radius</b>	20 mm
<b>Working Temperature</b>	-20 °C / +70 °C
<b>Conductor Resistance</b>	< 85 Ω/km
<b>Capacitance</b>	130 pF/m
<b>Insulation Resistance</b>	> 1 GΩ x km

Leiteraufbau	blanke Cu-Litze, 7 x 0,20 mm
Leiterquerschnitt	0.22 mm <sup>2</sup>
Aderisolation	PE
Einzeladerabschirmung	blanker Cu-Wendelschirm
Aderanzahl	2
Aderanordnung	parallel, aufreißbar
Außenmantel	PVC, matt
Abmessungen	4,0 x 8,0 mm
Min. Biegeradius	20 mm
Betriebstemperatur	-20 °C / +70 °C
Leiterwiderstand	< 85 Ω/km
Kapazität	130 pF/m
Isolationswiderstand	> 1 GΩ x km

■ black

Order Code Bestell-Nr.	Colour Farbe	Weight Gewicht	Standard Length [m] Standard Längen [m]	Max. Length / Reel Max. Länge / Spule
IY204	black	40 g/m	100 / 500	1000 m

Patch / Studio / Outdoor