

**balanced patch and microphone cable**

- very dense braid screen

PVC

Bantam (TT phone) patch cable, midi cable, stable microphone cable with ultra-low outer diameter - the MY204 is ideal for all these applications. Its braided shield offers superior tensile strength, making the MY204 suitable for uses such as XLR fan-outs or XLR patch panels. The MY204 features a copper drain wire in contact with the braided shield, which can significantly speed up custom cable production.

construction

cond. construction	stranded bare copper, 28 x 0.10 mm
cond. cross section	0.22 mm ²
insulation	polyethylene (PE)
core arrangement	2 cores + twisted cotton tracers
drain wire	stranded tinned copper, 28 x 0.10 mm
taping	PET fleece
shielding	tinned copper braid, 85% coverage
outer jacket	PVC, matt
overall diameter	4.6 mm

electric

conductor resistance	< 85 Ω/km
capacitance	
cond./cond.	75 pF/m
cond./shield	130 pF/m
insulation resistance	> 0.1 GΩ x km

mechanics

min. bending radius	25 mm
working temperature	-20°C / +70°C

order code	colour	weight [kg/m]	standard lengths [m]
MY204SW	black	0.03	50 / 100 / 200 / 300
MY204BL	blue	0.03	50 / 100 / 200 / 300
MY204RT	red	0.03	50 / 100 / 200 / 300
MY204GR	grey	0.03	50 / 100 / 200 / 300

technical specifications are subject to change