

The **M Cap® SUPREME Classic Silver-Gold.Oil** is definitely the top-of-the line model of our oil impregnated capacitors. In comparison with the Silver.Oil version, it technically features a further extended lifetime. More importantly, sonically the SilverGold.Oil version stands out due to its wonderful natural singing and exceptional micro dynamic, same time

Technical specifications:

Capacitance: 0.010µF-10µF
Dielectric: Polypropylene
Metallisation: 99.99% silver, 1% gold
Purity of silver: min. 99.97% typ. 99.99%
Purity of gold: min. 99.97% typ. 99.99%
Dielectric strength: 1 200V DC
Loss factor tan δ : 0.0002@1 kHz, 0.0001@10 kHz
Permissible ambient temperature 85°C/185°F



SUP.SGO

Supreme capacitors, SilverGold.Oil

Capacity [µF] ±2%	VDC	Body Ø * L [mm]	Wire Ø [mm]
0,010	1000	17 * 36	0,6 * 60
0,10	1000	17 * 36	1,0 * 60
0,22	1000	19 * 39	1,0 * 60
0,33	1000	19 * 39	1,0 * 60
0,47	1000	26 * 41	1,4 * 60
0,68	1000	26 * 41	1,4 * 60
1,0	1000	31 * 42	1,4 * 60
1,5	1000	36 * 42	1,4 * 60
2,2	1000	36 * 56	1,4 * 60
2,7	1000	36 * 56	1,4 * 60
3,3	1000	41 * 57	1,4 * 60
3,9	1000	41 * 57	1,4 * 60
4,7	1000	46 * 71	1,4 * 60
5,6	1000	46 * 71	1,4 * 60
6,8	1000	51 * 71	1,4 * 60
8,2	1000	51 * 71	1,4 * 60
10	1000	51 * 106	1,4 * 60

