

**AES/ EBU digital wiring cable**

- 0.22 mm² conductor cross section
- 110 Ohm characteristic impedance
- AL foil shield

PVC

The most frequent applications for this balanced cable are wiring of digital equipment and patch boards for professional audio engineering. The characteristic impedance of 110 ohm makes it suitable for digital symmetrical sound transmission according to the AES3 standard as well as the transmission of DMX signals. The use of foam polyethylene for core insulation results in a very compact outside diameter.

construction

cond. construction	stranded tinned copper, 7 x 0.20 mm
cond. cross section	0.22 mm ²
insulation	Foam-Skin PE
shielding	tinned stranded drain wire + AL/PETP foil
overall diameter	4.2 mm

mechanics

min. bending radius	25 mm
working temperature	-20°C / +70°C

electric

conductor resistance	< 85 Ω/km
capacitance	
cond./cond.	47 pF/m
characteristic impedance	110 Ω
attenuation [dB/100m]	
1 MHz	2.3
3 MHz	3.9
10 MHz	6.9
insulation resistance	> 10 GΩ x km
test voltage	
cond./cond.	1200 V
cond./shield	500 V

order code	colour	weight kg	standard lengths m
OTW204Y	black	0.02	50 / 100 / 200 / 300 / 500

technical specifications are subject to change