

**OmniWIRE - AES/ EBU multicore cable - n x 2 x 0.15 mm<sup>2</sup> - PVC**

- tinned copper spiral pair shields
- ultra flexible

**PVC**

The OW15Y OmniWIRE multicore cable is designed for maximum flexibility, with each wire made up of 19 individual wires. Colour coded cores are twisted in pairs and spiral shielded against interference. Shields are surrounded by black pair jackets. The OW15Y is available with between two and twenty-four pairs. It complies with the AES/EBU standard and is suitable for analogue and digital audio. The pairs are twisted in layers to ensure the cable retains its structure even under heavy mechanical stress, making it an ideal choice for mobile studio cabling. The OW15Y is enclosed in an ultra-flexible soft PVC outer jacket.

**construction**

cond. construction	stranded tinned copper, 19 x 0.10 mm
cond. cross section	0.15 mm <sup>2</sup>
insulation	Foam-Skin PE, KLOTZ multicore colour code
pair shielding	tinned copper shield
pair jacket	PVC, black, numbered
cable stranding	n pairs twisted in layers
taping	polyester-fleece
outer jacket	PVC

**mechanics**

min. bending radius	5x overall diameter
working temperature	-20°C / +70°C

**electric**

conductor resistance	< 125 Ω/km
capacitance	
cond./cond.	49 pF/m
characteristic impedance	110 Ω
attenuation [dB/100m]	
1 MHz	2.5
3 MHz	4.6
10 MHz	13.5
crosstalk attenuation	
15 kHz	> 100 dB
10 MHz	> 50 dB
insulation resistance	> 10 GΩ x km
test voltage	
cond./cond.	1200 V
cond./shield	500 V

order code	no. of pairs	outer Ø mm	colour	weight kg	standard lengths m
OW15Y02	2	8.0	black	0,065	10 / 20 / 50 / 100 / 200 / 300
OW15Y04	4	9.2	black	0,1	10 / 20 / 50 / 100 / 200 / 300
OW15Y08	8	11.7	black	0,165	10 / 20 / 50 / 100 / 200 / 300
OW15Y12	12	15.0	black	0,267	10 / 20 / 50 / 100 / 200 / 300
OW15Y16	16	16.6	black	0.34	10 / 20 / 50 / 100
OW15Y24	24	20.5	black	0.49	10 / 20 / 50 / 100

technical specifications are subject to change