

Section

Public Address

Category

EN 54-24 Loudspeakers

Code

C96/15-EN, C96/15N-EN

Certificates

Application-specific standards: EN 54-24:2008, IEC 268-5

Description

15 W 2-way monitorbox

This compact monitor speaker has a sophisticated design and a powerful sound. It is perfectly suitable for installations where high sound quality is needed. The 15 W speaker is equipped with a high quality 2-way system and a 100 V transformer with 3 power adjustments. The impact & UV-resistant ABS plastic housing assures enduring stability. For additional reliability, the wetness impregnation of the speaker chassis is provided. The speaker is also secured with protection class **IP 33C** against the risks of environmental influences. A comfortable connection of the speaker is made possible by a stable screw terminal with contact protection. Quick and easy installation with wall mounting bracket.



C96/15-EN

C96/15N-EN

Technical data

Rated power	15 W
Adjustable power	15 - 7,5 - 3,75 - 1,8 W / 8 Ω
SPL sound pressure level	94,2 dB
Sensitivity	82,5 dB
Frequency response	82 ÷ 23.500 Hz
Dispersion angle	132° (H) / 115° (V)
Protection degree	IP 33C
Mounting	Swivelling bracket
Connection	6-pin screw terminal
Colour	White (C96/15-EN) Black (C96/15N-EN)
Dimensions (W x H x D)	130 x 210 x 120 mm
Net weight	1,70 kg

