

# TZ-200BS-EB

TOA's column speaker TZ-400BS is the first-rate choice for all applications with a necessity of excellent speech intelligibility: lecture rooms, houses of worship, auditoriums, all places with important public announcements. This elegant 2-way-speaker provides crisp sound due to a built-in tweeter and are designed to give superb audio. The remarkably slim profile can not only be integrated unobtrusively into every interior setting, but also outside due to its IP66 protected weatherproof housing and additional wide temperature range. With its wide horizontal and narrow vertical dispersion, the speaker can be installed even in acoustically challenging environments.



Article number: TZ-200BS-EB  
Alternative products: TZ-400BS-EB

## Specifications

Audio input	Screw terminal (steatite), 4 ports
Sensitivity (1#V, 1#m)	92 dB
Frequency response.	130 Hz - 20 kHz (peak -20 dB)
Max. SPL (1 m)	105 dB (20W, 1m, 100 10 kHz, pink noise)
Tappings	100V line: 20W (500Ω), 10W (1kΩ), 5W (2kΩ) 70V line: 10W (500Ω), 5W (1kΩ), 2.5W (2kΩ)
Speaker component	Woofer: 8,9cm x 4, Tweeter: 8,2 x 1cm
Finish.	Aluminium, paint, traffic white (RAL 9016 or equivalent),
Operating temperature.	-30°C ~ +60°C



TZ series

# TZ-200BS-EB

---

Appearance