

the ELEKTRALITE PaintCan 750

Paintcan 750 is a multi-talented fixture which can be used in theaters, churches, arenas, retail displays, installations or in touring/rental applications.

With reduced noise levels due to an intelligent fan system that operates in response to internal temperature, the Paintcan 750 can be used in the quietest of venues.



Paintcan 750 can utilize a variety of 750 lamp sources, all of which are 3200K in color temperature.

Ideal for warm coloring and excellent flesh tones. No cold light here.

It's powerful 750 lamp can project long throws where so many other fixtures fail, but power consumption has been minimized by use of ultra efficient transformers and electronic components. So green can be more than just a color.

Paintcan 750 has full color mixing, a 20 to 40 degree zoom, beam shaping, and an electronic (not mechanical!) dimmer.

Most importantly, it is also very affordable.

Paintcan 750 can also be set to run automatically so no need for controller and signal cables. It's in-built flash memory makes it ideally suited for product displays in retail stores or for product launches.



ELEKTRALITE

PaintCan 750	
Lamp	Osram GLD750 3200K
Pan / Tilt	Manually adjustable
Beam Output	20° ~ 40° Full Electronic Zoom
Dimmer	Full electronic dimming [0 ~ 100%]
Color	
color wheels	1 rotating bidirectional wheel with removable and interchangeable color filters
colors	Close, Open (white), Deep Red (R26)* ¹ , Blue (R80)* ¹ , Yellow (R15)* ¹ , Amber (R22)* ¹ and CTB
mixing	Full CMY mixing [0 ~ 100% Cyan / Yellow / Magenta]
Effects	
beam	Beam shaping with full frost filter
strobe / shutter effects	Shutter close / open, Strobe effect slow to fast
programmed effects	8 internal programs
Electronics / Control	
external lamp control	Yes
super—quiet cooling	Yes — Variable speed cooling fans controlled by internal sensor circuitry with manual override
display	DMX address, Individual dmx channel value, Lamp hours, Fixture hours, Display reverse, Channel control and test w/o controller, Reset/home, Display on/off, Fan control high/auto/low speed, color mixing adjustment for compatibility with multiple fixtures, preheat adjustment for lamp
master / slave	Yes
internal memory	Up to 48 cues can be programmed onto the PaintCan 750's internal flash memory with or without a controller. The cues can be recalled without a controller
sound activation	Operates in stand alone mode with either automatic programs or by audio trigger
N° DMX channels	9
DMX Connectors	5 pin Male and Female XLR connectors
Electrical	
voltage	100V, 115V and 230V selectable
power consumption	7.5A @ 115V / 3.75A @ 230V
Weight & Dimensions	35lb / 15.9kg
Finish	Available in Black or White finish
Accessories	Barndoor, Fiber optic harness plate
Certification	ETL Certified model available
Notes	* ¹ Color swatches based on subjective evaluation

Elektralite

Group One Limited

70 Sea Lane . Farmingdale . 11735 . USA

T +1 516 249 3662 . **F** +1 516 249 8870 . **W** www.myelektralite.com . **E** info@myelektralite.com

In a policy of continual improvement features subject to change . Copyright © Elektralite, 2011 [EL_BRC_110208_0001]